



MINIATURE HIGH PRESSURE PRESSURE TRANSDUCER

HKM-312 (M) SERIES

- Excellent Stability
- All Welded Construction
- Robust Construction
- Silicon on Silicon Integrated Sensor **VIS**[®]
- High Natural Frequencies
- 5/16-24 UNF-2A or M8 X 1 Thread
- Intrinsically Safe Applications Available (i.e. IS-HKM-312)




The HKM-312 is a miniature threaded pressure transducer. The hexagonal head and o-ring seal make it easy to mount and simple to apply.

The HKM-312 utilizes a flush metal diaphragm as a force collector. A solid state piezoresistive sensing element is located immediately behind this metal diaphragm which is protected by a metal screen. Force transfer is accomplished via non-compressible silicone oil. This sensing sub assembly is welded to a stainless steel body.

This advanced construction results in a highly stable, reliable and rugged instrument with all the advantages of microcircuitry: significant miniaturization, excellent repeatability, low power consumption, etc. The miniaturization process also yields a marked increase in the natural frequencies of the transducers, making them suitable for use even in shock pressure measurements.

Kulite recommends the [KSC-2](#) signal conditioner to maximize the measurement capability of the HKM-312 transducer.



	35 500	70 1000	170 2500	350 5000	700 BAR 10000 PSI
INPUT					
Pressure Range					
Operational Mode	Absolute, Sealed Gage				
Over Pressure	2 Times Rated Pressure				
Burst Pressure	3 Times Rated Pressure				
Pressure Media	Any Liquid or Gas Compatible With 15-5 PH or 316 Stainless Steel (All Media May Not Be Suitable With O-Ring Supplied)				
Rated Electrical Excitation	10 VDC/AC				
Maximum Electrical Excitation	12 VDC/AC				
Input Impedance	1000 Ohms (Min.)				
OUTPUT					
Output Impedance	1000 Ohms (Nom.)				
Full Scale Output (FSO)	100mV (Nom.)				
Residual Unbalance	± 5 mV (Typ.)				
Combined Non-Linearity, Hysteresis and Repeatability	± 0.1% FSO BFSL (Typ.), ± 0.5% FSO (Max.)				
Resolution	Infinitesimal				
Natural Frequency of Sensor Without Screen (KHz) (Typ.)	Greater Than 400 KHz				
Acceleration Sensitivity % FS/g Perpendicular	1.1x10 ⁻⁴	6.2x10 ⁻⁵	2.4x10 ⁻⁵	1.5x10 ⁻⁵	1.3x10 ⁻⁵
Insulation Resistance	100 Megohm Min. @ 50 VDC				
ENVIRONMENTAL					
Operating Temperature Range	-20°F to +250°F (-29°C to +120°C)				
Compensated Temperature Range	+80°F to +180°F (+25°C to +80°C) Any 100°F Range Within The Operating Range on Request				
Thermal Zero Shift	± 1% FS/100° F (Typ.)				
Thermal Sensitivity Shift	± 1% /100° F (Typ.)				
Linear Vibration	10-2,000 Hz Sine, 100g. (Max.)				
Mechanical Shock	20g half Sine Wave 11 msec. Duration				
PHYSICAL					
Electrical Connection	4 Conductor 26 AWG Shielded Cable 36" Long				
Weight	15 Grams (Max.) Excluding Cable				
Pressure Sensing Principle	Fully Active Four Arm Wheatstone Bridge Dielectrically Isolated Silicon on Silicon				
Mounting Torque	50 Inch-Pounds (Max.) 6 Nm				

Note: Custom pressure ranges, accuracies and mechanical configurations available. Dimensions are in inches. Dimensions in parenthesis are in millimeters. All dimensions nominal. (G) Continuous development and refinement of our products may result in specification changes without notice. Copyright © 2014 Kulite Semiconductor Products, Inc. All Rights Reserved. Kulite miniature pressure transducers are intended for use in test and research and development programs and are not necessarily designed to be used in production applications. For products designed to be used in production programs, please consult the factory.